

DSC-P92

Cyber-shot® Digital Still Camera



FEATURES

▶ 1/1.8" 5.0 Megapixel Effective Super HAD™ CCD



Super HAD (Hole Accumulation Diode) CCD's provide excellent image quality by allowing more light to pass to each pixel, increasing sensitivity and reducing noise.

3X Optical Zoom Lens



To help frame your shots for better digital pictures. Optical Zoom helps you bring distant subjects closer & pull back for wide shots.

▶ 0 - 4.0X Smart Zoom (at VGA Size)



Smart Zoom intelligently uses the full CCD to let you zoom into the portion of interest by cropping the image size—thus avoiding the image degradation of Digital Zooms.

3 Area Multi-Point Auto Focus



Evaluating 3 separate focus areas of the frame, Multi-Point AF can intelligently focus on the subject and avoid mistakenly focusing on the background.

AF (Auto Focus) Illuminator



Briefly illuminating the subject in low- or no-light conditions, AF Illuminator helps establish a positive focus lock.

Multi-Pattern Measuring



Independently light-metering 49 points of the frame, Multi-Pattern Measuring establishes the optimum exposure value, even in scenes where pronounced highlight and shadow are not centered in the frame.

Auto Daylight Synchro Fill Flash

If the Multi-Pattern Measuring system determines the subject is backlit or in shadow, fill flash automatically fires to provide optimum exposure.

Memory Stick® Media



Digital. Powerful. Transportable.™ Memory Stick media is compact, portable and rugged—connecting a variety of hardware and software applications.

Scene Selection Mode



With 5 Scene Modes, camera parameters can be matched to the shooting conditions. Twilight, Twilight Portrait, Landscape, Snow and Beach presets make it easy to optimize difficult shooting environments.

Slow Shutter Noise Reduction



During long Twilight mode exposures, Slow Shutter NR captures the scene, and then the CCD noise pattern with a dark frame exposure. By subtracting the two, even long exposures can be clear.

14-Bit DXP A/D Conversion



Sony's 14-bit Digital Extended Processor captures the range between highlight and shadow with up to 16,384 values, for extended dynamic contrast and detail.

1.5" LCD Monitor

Monitors the scene for accurate framing. 123K pixel and anti-glare coating help provide excellent viewing and image playback clarity, even outdoors.

True Zoom Optical Viewfinder

Provides accurate framing at eye level, great for added stability and following fast moving subjects.

Pre-Flash Metering

With a momentary pre-flash, the camera illuminates the subject and sets exposure through the lens for accurate flash metering. Adjustable flash level and red-eye reduction insure great flash shots.

5MP (2592 x 1944) Image Size

With its high resolution CCD, the DSC-P92 captures in 4 different image sizes, with selectable Fine or Standard JPEG compression.

Multi-Burst Mode



Captures 16 320x240 frames as part of a single 1280x960 image which plays back sequentially in the camera. Selectable 1/7.5, 1/15, 1/30 second frame intervals provide convenient motion analysis.

MPEG Movie VX Mode



Captures VGA (640x480) high frame rate (16 frames per second) audio/video clips with length limited only by the capacity of the media. Video Mail mode captures smaller file sizes suitable for email.

Clip Motion Mode



Capture up to 10 images and convert them to an animated GIF with 2 fps playback. By varying the interval between shots you can create animations not possible with other motion capture modes.

Playback Zoom, Trim and Resize



During playback, magnify any portion of the image up to 5X and trim to the area of your interest. Then, save the new image as a new file in any of the image sizes available from the menu.

Rechargeable NiMH Batteries



Long-lasting power is provided by 2100 mAh rated Nickel Metal Hydride (NiMH) Stamina® batteries with BC-CS2 external charger. Or, choose "AA" Alkaline cells or optional AC adaptor.

ADDITIONAL FEATURES

2 Shot Burst Mode	Video Output (PAL/NTSC Selectable)
Clear Color/Clear Luminance NR	4 Mode In-Camera Picture Effects
MPEG1 Cue, Review and Divide	5 Step Manual preset Focus
3:2 Aspect Ratio Mode	

SPECIFICATIONS

Imaging Device: 1/1.8" 5.0 Megapixel Effective Super HAD™ CCD

Recording Media: Memory Stick® Media, Memory Stick PRO™ Media

Zoom: 3X Optical, 4X Smart Zoom (at VGA size), 12X Total

Filter Diameter: N/A

Focal Length: 7.9 - 23.7mm

35mm Equivalent: 38 - 114mm

Aperture: f2.8 - 5.6

Focus: 3 Area Multi-Point AF, 5 Step Manual Preset

Minimum Focus Distance: 19.7" (50 cm)

Macro Focus Distance: 3.9" (10 cm) Shutter Speed:

Shutter Speed: Auto, 1/30 - 1/2000 sec, Twilight 2 sec - 1/2000

Manual Exposure: ±2.0 EV, 1/3 EV Steps

Color LCD: 1.5" 123K Pixels Low Temperature Polysilicon TFT

Flash Modes: Auto/Forced On/Forced Off/Slow Synchro

Red-Eye Reduction: On/Off

Flash Effective Range: 1.3 - 12.5 ft (0.4 - 3.8m)

White Balance: Auto, Daylight, Cloudy, Fluorescent, Incandescent

Picture Effects: Black & White, Solarize, Sepia, Negative Art

ISO: Auto, 100, 200, 400

Scene Modes: Twilight, Twilight Portrait, Landscape, Beach, Snow

Self Timer: Yes, 10 Seconds

Video Output: Yes NTSC/PAL Selectable

Still Image Modes: JPEG (Fine/Std.), Burst, Email, Voice Memo

MPEG Movie Modes:

MPEG VX (640x480, 16fps, with audio)

MPEG Video Mail (160x112, 8 fps with audio)

Clip Motion: Normal (160x120), Mobile (80x72)

Microphone/Speaker: Yes/Yes

USB Terminal: Yes Supports USB 2.0

Memory Stick PRO™ Media Compatibility: Tested to support up to 1GB media capacity; does not support high speed transfer function; does not support Access Control security function

Battery Type/Capacity: NiMH AA, 2100 mAh Rated

Supplied Software: Pixela™ Image Mixer Software for Sony v1.5, USB Driver SPVD-008

OS Compatibility: Microsoft® Windows® 98/98SE/Me/2000 Professional/XP Home/Pro; Macintosh® OS 8.5.1/8.6/9.0/9.1/9.2

Supplied Accessories: NH-AA-DA Rechargeable NiMH Batteries, BC-CS2 NiMH Battery Charger, AV and USB Cables, Wrist Strap, MSA-16A 16MB Memory Stick® Media, Software CD-ROM

Dimensions (W/H/D): 4 11/16" x 2 1/4" x 1 5/16" (119.5 x 57.7 x 32.6mm)

Weight: 9.5 oz (259g) (w/Battery, Memory Stick® Media, Strap)

SONY

Sony Electronics Inc.
16765 West Bernardo Drive
San Diego, Ca 92127
www.sony.com/di



JPEG Still Image Mode

Fine/Standard Picture Quality

Memory Stick® Media¹	2592x1944 (5MP)	2592x1728 (3:2)	2048x1536 (3MP)	1280x960 (1MP)	640x480 (VGA)	
16MB	6/11	6/11	10/18	24/46	97/243	
32MB	12/23	12/23	20/37	50/93	196/491	
64MB	25/48	25/48	41/74	101/187	394/985	
128MB	51/96	51/96	82/149	202/376	790/1,975	
Memory Stick PRO™ Media¹	256MB	92/174	92/174	148/264	357/649	1,428/3,571
512MB	188/354	188/354	302/537	726/1,320	2,904/7,261	
1GB	384/723	384/723	617/1,097	1,482/2,694	5,928/14,821	

MOTION CAPTURE MODES

Maximum Recording Time (minutes/seconds)

Memory Stick® Media	MPEG Movie		Clip Motion (Images)		16 Frame Multi-Burst 1280x960 (Fine/Std)	
	640x480 (VX Mode)	160x112 (Mail Mode)	160x112 (Normal-10f)	80x72 (Mobile-2f)		
16MB	42sec	11m 13s	88	486	24/46	
32MB	87sec	22m 43s	178	982	50/93	
64MB	176sec	45m 40s	358	1,971	101/187	
128MB	5m 54s	91m 34s	718	3,951	202/376	
Memory Stick PRO™ Media	256MB	10m 41s	165m 35s	1,190	3,571	357/649
512MB	21m 44s	336m 43s	2,420	7,261	726/1,320	
1GB	44m 23s	687m 19s	4,940	14,821	1,482/2,694	

BATTERY LIFE (Approx)

Battery Fully Charged	Recording-# Shots* LCD On/Off	Recording-Minutes* LCD On/Off	Viewing** No. Images/Batt. Life
NH-AA-DA	300/500	150min/250min	5400/270min

*Under Average Conditions:

Normal Mode (JPEG), Picture quality Fine; Shooting each image at 30 second intervals; Zoom is alternated from Wide to Telephoto ends; Flash operated every other shot; Power is turned on/off after every 10 shots; Actual results may vary on conditions of use.

**Viewing single images consecutively, at about 3 second interval.

OPTIONAL ACCESSORIES

ACC-3NP Starter Kit (AC-LS5, LCS-CP2, NH-AA-2DA, BC-CSQ)	MSA-32A, MSA-64A, MSA-128A Memory Stick® Media
NH-AA-2DA/4DA Rechargeable NiMH Batteries (2pk/4pk)	MSA-128S2 Memory Stick® Media with Select Function (256MB total)
AC-LS5 AC Power Supply	MSX-256, MSX-512, MSX-1G Memory Stick PRO™ Media
LCS-PEA Soft Carrying Case	MSAC-HGA8 Memory Stick® Media Carrying Case
LCS-CP2 General Carrying Case	MSAC-US70 Memory Stick PRO™ Media USB Adaptor/Mouse
LCS-CSB Sport Style Carrying Case	MSAC-US20 Memory Stick PRO™ Media USB Adaptor
HVL-FSL1A External Slave Flash w/Bracket	MSAC-PC3 Memory Stick PRO™ Media PC Card Adaptor
VAD-PEA Conversion Lens Adaptor Mount	VMC-14UMB Replacement USB Cable
VCL-DH0730 Wide Angle Conversion Lens*	VCT-MTK Travel Tripod
VCL-DH1730 Telephoto Conversion Lens*	VCT-R640 Lightweight Tripod
VF-30CPKS Polarizing Filter Kit*	
VF-30NK Neutral Density Filter Kit*	
VF-30SC Special Effects Filter Kit*	

©2003 Sony Electronics Inc.

Reproduction in whole or in part without written permission is prohibited. All rights reserved.

Sony Cyber-shot, Digital, Powerful, Transportable, Memory Stick, Memory Stick PRO, the Memory Stick logo, Stamina and Super HAD are trademarks of Sony. Microsoft and Windows are trademarks of Microsoft Corporation. Macintosh is a trademark of Apple Computer, Inc. All other trademarks are property of their respective owners. Features and specifications subject to change without notice. Non-metric weights and measures are approximate.

¹ Available storage capacity of Memory Stick and Memory Stick PRO media may vary. A portion of the memory is used for data management functions.