

CPD-G520

Multiscan® G520 Computer Display

SONY



- *21" (19.8" VIS) Flat Trinitron CRT* – Visually flat screen delivers outstanding image quality with reduced glare.
- *Digital Multiscan technology* – Supports resolutions up to 2048 x 1536.
- *0.24mm Aperture grille pitch* – Sets new standard in image clarity and precision.
- *Picture effect* – Boosts image luminance to optimize performance for graphics and video applications.
- *HiDensity™ Electron Gun with Enhanced Elliptical Correction System™ technology* – Ensures consistent, accurate focus across the entire screen, even in the corners.
- *Dual inputs* – Two HD-15 connectors support multiple PC usage.

Flat Trinitron® CRT and advanced Multiscan® technology combine with improved OSD controls to deliver a full featured display with superb image performance.

Complements the corporate and home workplace with space saving features and a new cabinet design in two-toned gray.




Flat Trinitron CRT
The definition of definition™

CPD-G520

Multiscan® G520 Computer Display


SONY

Dual Inputs



- Multiple PC usage support (HD15)

Smart Cable™ Design



- Eases cable connections.
- Allows unit to be flush to wall.

Display Mouse™ Controls



- Simple set-up & adjustment

Model	CPD-G520
Color	Two Toned Gray
CRT	Super Fine Pitch 21" Flat Trinitron®

Viewable Image Size	19.8"
----------------------------	-------

Aperture Grille Pitch	0.24 mm
------------------------------	---------

Screen Treatment	High Contrast AR Coating
-------------------------	--------------------------

Horizontal Scan	30kHz - 130kHz
------------------------	----------------

Vertical Refresh	48Hz - 170Hz
-------------------------	--------------

Maximum Resolution	2048 x 1536
---------------------------	-------------

Recommended Resolutions	1800 x 1440 @ 85Hz, 1600 x 1200 @ 85Hz 1280 x 1024 @ 85Hz
--------------------------------	--

Factory Preset Timings	Timing Data Table (TDT) - 27 modes User Adjustable - 15 Settings
-------------------------------	---

Color Temperature Presets	5000, 6500, 9300 (default) Kelvin 5000K~11000K adjustable, sRGB Mode Variable RGB Gain and Bias control
----------------------------------	---

Video Signal Inputs	
Video Input	Analog RGB 0.7 Vp-p ± 5%, Positive, 75 ohms (typ)
Sync Input	Separate HD/VD or Ext. Composite Logic Level "1" 2.4 - 5.5V Logic Level "0" 0.0 - 0.5V Polarity free, 2.2k ohms
Sync on Grn	0.3 Vp-p ± 10%, Negative

Input Connectors	D-sub HD15 x 2
-------------------------	----------------

Display Dimensions (HxWxD)	19.7" x 19.6" x 19.1"
-----------------------------------	-----------------------

Display Weight	67.4 lbs
-----------------------	----------

Power Requirements	90-264V AC, 50/60 Hz
---------------------------	----------------------

Power Management:	
Normal Operation	135 W max.
Active Off	3 W max.
Power Off	Approx. 0 W

Operating Conditions	
Temperature:	50° to 104° F (10° to 40° C)
Relative Humidity:	10% to 80% (Non-Condensing)

Shipping Conditions	
Temperature:	-40° to 140°F (-40° to 60°C)
Relative Humidity:	5% to 95% (Non-Condensing)

Regulation and Standard Compliance	
Safety Regulations	UL 1950, cUL DHHS, DNHW, NOM (Mexico) TUV GS
Emissions/EMI	FCC Class B, IC Class B TCO 99
Others	TUV Ergonomie
Power Management Designed for	International Energy Star PC99, Windows® 95,98,2000 Windows NT®, Macintosh® Compatible
Plug and Play	DDC-2B, DDC-2Bi

Tilt / Swivel	
Tilt Range	-5° to +15°
Swivel Range	± 90°

Front Panel User Controls	
Power Switch	On/Off
Menu Button	Enter / Exit On Screen Display
Control Button	Navigate OSD and adj Contrast
Picture Effect Button	Professional/Standard/Dynamic
Input Selector	1 or 2

On Screen Display Controls	
Contrast / Brightness Size / Center	Contrast, Brightness Auto Size and Centering H Center, H Size V Center, V Size
Geometry	Raster Rotation Pincushion, Pin Balance Key Stone, Key Balance
Convergence	H & V Convergence V Top & V Bottom Conv.
Screen	Degauss, Moiré Adjust Landing Adjust
Color Preset Color Adjust	5000K / 6500K / 9300K 5000K ~ 11000K adjustable RGB Gain and Bias Control sRGB Mode
Option	Image Restoration Control Lock, OSD Position Color Mode Select
OSD Language	(Eng., Fre., Ger., Spa., Ita., Dut., Swe., Rus., Jap.)
Reset	Mode Reset, All Reset

Supplied Accessories	
AC Power Cord	
HD15 - HD15 Video Signal Cable	
User's Manual (English, French, Spanish)	
Warranty Card	
Notes on cleaning screen surface	

Limited Warranty	
Parts, CRT and Labor: 3 years	



SONY

Sony Electronics Inc.
16765 West Bernardo Drive
California 92127
For more information: 1.800.352.SONY
Web address: <http://www.sony.com/displays>
Printed in the USA - (04/01/01)

Computer Interface: The computer industry lacks standards, and therefore, there are a multitude of varying software packages and add-on hardware options. This display is not manufactured to any specific software, and Sony does not and cannot make any warranty or representation with respect to the performance of this product with any particular software packages and/or non-Sony add-on hardware option except those mentioned in this document. Sony hereby disclaims any representations or warranty that this product is compatible with any combination of non-Sony products you may choose to connect. While Sony representatives or Sony authorized dealers may be able to assist you and may make recommendations, they are NOT authorized to vary or waive this disclaimer. Purchasers must determine for themselves the suitability and compatibility of the hardware and software in each and every particular instance.

©2000 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, the Sony logo, DisplayMouse, Trinitron, Multiscan, Digital FlexRes, Auto ImageSet and Zero Footprint Design™ are trademarks of Sony. Microsoft, the Windows Logo and Windows are registered trademarks of Microsoft Corporation. Mac and Macintosh are trademarks of Apple Inc. All other trademarks are property of their respective owners. Features and specifications are subject to change without notice. Non-metric weights and measurements are approximate.

This monitor is Energy Star Compliant when used with a computer equipped with VESA Display Power Management Signaling (DPMS). As an International Energy Star Partner, Sony Corporation has determined that this product meets the International Energy Star Program for energy efficiency. The Energy Star emblem does not represent EPA endorsement of any product or service. Screen images are simulated.